Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No. : 817149
V004.0

LOCTITE 243

Revision: 11.06.2026
printing date: 14.11.2026
Replaces version from: 10.11.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier
LOCTITE 243
UFI: 63X3-WXKC-W209-MCAQ

1.2. Relevant identified uses of the substance or mixture and uses advised against
Intended use:
Threadlocker

1.3. Details of the supplier of the safety data sheet
Henkel Ltd
Adhesives
Wood Lane End
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com
For Safety Data Sheet updates please visit our website www.mysds.henkel.com or www.henkel-adhesives.com.

1.4. Emergency telephone number
24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin sensitizer	Category 1
H317 May cause an allergic skin reaction.	
Chronic hazards to the aquatic environment	Category 3
H412 Harmful to aquatic life with long lasting effects.	

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains Tetramethylene dimethacrylate

2,2'-Ethylenedioxydiethyl dimethacrylate

Ethylene glycol methacrylate maleate
maleic anhydride

Signal word:	Warning
Hazard statement:	H317 May cause an allergic skin reaction. H412 Harmful to aquatic life with long lasting effects.
Precautionary statement:	"***" ***For consumer use only: P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P501 Dispose of contents/container in accordance with national regulation.***
Precautionary statement: Prevention	P273 Avoid release to the environment. P280 Wear protective gloves.
Precautionary statement: Response	P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration ≥ the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

None

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS No. EC No UK-REACH-Reg. No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Tetramethylene dimethacrylate 2082-81-7 218-218-1	20- < 40 %	Skin Sens. 1B, H317		
2,4,6-Triallyloxy-s-triazine 101-37-1 202-936-7	5- < 10 %	Acute Tox. 4, H302 Aquatic Chronic 2, H411		
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0 203-652-6	1- < 5 %	Skin Sens. 1B, H317	dermal:ATE = > 5.000 mg/kg inhalation:ATE = 28,17 mg/l;dust/mist	
Ethylene glycol methacrylate maleate 51978-15-5 257-569-5	0,1- < 1 %	Skin Sens. 1, H317 Skin Corr. 1B, H314 Eye Dam. 1, H318		
methacrylic acid 79-41-4 201-204-4	0,1- < 1 %	Acute Tox. 4, H302 Acute Tox. 3, H311 Acute Tox. 4, H332 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335	STOT SE 3; H335; C >= 1 % ===== dermal:ATE = 500 mg/kg inhalation:ATE = 3,19 mg/l;dust/mist	
maleic anhydride 108-31-6 203-571-6	0,001- < 0,01 % (10 ppm- < 100 ppm)	STOT RE 1, Inhalation, H372 Acute Tox. 4, H302 Skin Sens. 1A, H317 Resp. Sens. 1, H334 Eye Dam. 1, H318 Skin Corr. 1B, H314	Skin Sens. 1A; H317; C >= 0,001 %	

The product contains synthetic polymer microparticles above the concentration limit, but derogation §4 or §5 apply.
(4a) use at industrial sites

Generic Polymer Name	Concentration range
Polymers of propylene or of other olefins	0,1-10 %

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.
For full text of the H - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:
Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:
Rinse with running water and soap.
Obtain medical attention if irritation persists.

Eye contact:
Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:
Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed
SKIN: Rash, Urticaria.

Prolonged or repeated contact may cause eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed
See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media
Suitable extinguishing media:
water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:
High pressure waterjet

5.2. Special hazards arising from the substance or mixture
In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters
Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:
In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Avoid contact with skin and eyes.
Wear protective equipment.
Ensure adequate ventilation.
Keep away from sources of ignition.

6.2. Environmental precautions
Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up
Dispose of contaminated material as waste according to Section 13.
For small spills wipe up with paper towel and place in container for disposal.
For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections
See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling
Avoid skin and eye contact.
See advice in section 8

Hygiene measures:
Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.
Good industrial hygiene practices should be observed.

7.2. Conditions for safe storage, including any incompatibilities
Ensure good ventilation/extraction.
Keep container tightly sealed.
Refer to Technical Data Sheet.

7.3. Specific end use(s)
Threadlocker

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m³	Value type	Short term exposure limit category / Remarks	Regulatory list
Silane, dichlorodimethyl-, reaction products with silica 7631-86-9 [SILICA, AMORPHOUS, RESPIRABLE DUST]		2,4	Time Weighted Average (TWA):		EH40 WEL
Silane, dichlorodimethyl-, reaction products with silica 7631-86-9 [SILICA, AMORPHOUS, INHALABLE DUST]		6	Time Weighted Average (TWA):		EH40 WEL
Silane, dichlorodimethyl-, reaction products with silica 7631-86-9 [Dust, inhalable dust]		10	Time Weighted Average (TWA):		EH40 WEL
Silane, dichlorodimethyl-, reaction products with silica 7631-86-9 [Dust, respirable dust]		4	Time Weighted Average (TWA):		EH40 WEL
Ethene, homopolymer 9002-88-4 [Dust, inhalable dust]		10	Time Weighted Average (TWA):		EH40 WEL
Ethene, homopolymer 9002-88-4 [Dust, respirable dust]		4	Time Weighted Average (TWA):		EH40 WEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	20	72	Time Weighted Average (TWA):		EH40 WEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	40	143	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL
Maleic anhydride 108-31-6 [MALEIC ANHYDRIDE]		1	Time Weighted Average (TWA):		EH40 WEL
Maleic anhydride 108-31-6 [MALEIC ANHYDRIDE]		3	Short Term Exposure Limit (STEL):	15 minutes	EH40 WEL

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m³	Value type	Short term exposure limit category / Remarks	Regulatory list
Silane, dichlorodimethyl-, reaction products with silica 7631-86-9 [DUSTS NON-SPECIFIC]		10	Time Weighted Average (TWA):		IR_OEL
Silane, dichlorodimethyl-, reaction products with silica 7631-86-9 [SILICA, AMORPHOUS]		2,4	Time Weighted Average (TWA):		IR_OEL
Silane, dichlorodimethyl-, reaction products with silica 7631-86-9 [SILICA, AMORPHOUS]		6	Time Weighted Average (TWA):		IR_OEL
Silane, dichlorodimethyl-, reaction products with silica 7631-86-9		4	Time Weighted Average (TWA):		IR_OEL

[DUSTS NON-SPECIFIC]					
Ethene, homopolymer 9002-88-4 [Dusts non-specific]		10	Time Weighted Average (TWA):		IR_OEL
Ethene, homopolymer 9002-88-4 [Dusts non-specific]		4	Time Weighted Average (TWA):		IR_OEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	20	70	Time Weighted Average (TWA):		IR_OEL
Methacrylic acid 79-41-4 [METHACRYLIC ACID]	40	140	Short Term Exposure Limit (STEL):	15 minutes	IR_OEL
Maleic anhydride 108-31-6 [MALEIC ANHYDRIDE]	0,01		Time Weighted Average (TWA):		IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Tetramethylene dimethacrylate 2082-81-7	aqua (freshwater)		0,043 mg/l				
Tetramethylene dimethacrylate 2082-81-7	aqua (marine water)		0,004 mg/l				
Tetramethylene dimethacrylate 2082-81-7	aqua (intermittent releases)		0,098 mg/l				
Tetramethylene dimethacrylate 2082-81-7	sewage treatment plant (STP)		2 mg/l				
Tetramethylene dimethacrylate 2082-81-7	sediment (freshwater)				3,12 mg/kg		
Tetramethylene dimethacrylate 2082-81-7	sediment (marine water)				0,312 mg/kg		
Tetramethylene dimethacrylate 2082-81-7	Soil				0,573 mg/kg		
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	aqua (freshwater)		0,007 mg/l				
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	aqua (marine water)		0,001 mg/l				
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	Freshwater - intermittent		0,07 mg/l				
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	sediment (freshwater)				0,173 mg/kg		
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	sediment (marine water)				0,017 mg/kg		
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	Soil				0,057 mg/kg		
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	sewage treatment plant (STP)		10 mg/l				
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	oral				0,119 mg/kg		
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	aqua (freshwater)		0,164 mg/l				
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	aqua (marine water)		0,0164 mg/l				
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	sewage treatment plant (STP)		10 mg/l				
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	aqua (intermittent releases)		0,164 mg/l				
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	sediment (freshwater)				1,85 mg/kg		
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	sediment (marine water)				0,185 mg/kg		
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Soil				0,274 mg/kg		
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Air						no hazard identified
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Predator						no potential for bioaccumulation
methacrylic acid 79-41-4	aqua (freshwater)		0,82 mg/l				
methacrylic acid 79-41-4	Freshwater - intermittent		0,45 mg/l				
methacrylic acid 79-41-4	aqua (marine water)		0,082 mg/l				
methacrylic acid 79-41-4	sewage treatment plant (STP)		100 mg/l				
methacrylic acid 79-41-4	sediment (freshwater)				3,09 mg/kg		
methacrylic acid 79-41-4	sediment (marine water)				0,309 mg/kg		

methacrylic acid 79-41-4	Soil				0,137 mg/kg		
methacrylic acid 79-41-4	Predator						no potential for bioaccumulation
maleic anhydride 108-31-6	aqua (freshwater)		0,038 mg/l				
maleic anhydride 108-31-6	aqua (marine water)		0,004 mg/l				
maleic anhydride 108-31-6	Soil				0,037 mg/kg		
maleic anhydride 108-31-6	sediment (freshwater)				0,296 mg/kg		
maleic anhydride 108-31-6	sediment (marine water)				0,03 mg/kg		
maleic anhydride 108-31-6	sewage treatment plant (STP)		44,6 mg/l				
maleic anhydride 108-31-6	Freshwater - intermittent		0,379 mg/l				
maleic anhydride 108-31-6	Marine water - intermittent		0,038 mg/l				

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Tetramethylene dimethacrylate 2082-81-7	Workers	dermal	Long term exposure - systemic effects		4,2 mg/kg	
Tetramethylene dimethacrylate 2082-81-7	Workers	inhalation	Long term exposure - systemic effects		14,5 mg/m3	
Tetramethylene dimethacrylate 2082-81-7	General population	inhalation	Long term exposure - systemic effects		4,3 mg/m3	
Tetramethylene dimethacrylate 2082-81-7	General population	dermal	Long term exposure - systemic effects		2,5 mg/kg	
Tetramethylene dimethacrylate 2082-81-7	General population	oral	Long term exposure - systemic effects		2,5 mg/kg	
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	Workers	inhalation	Acute/short term exposure - systemic effects		134,4 mg/m3	
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	Workers	dermal	Long term exposure - systemic effects		1,5 mg/kg	
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	Workers	inhalation	Long term exposure - systemic effects		2,12 mg/m3	
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	General population	inhalation	Long term exposure - systemic effects		0,52 mg/m3	
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	General population	dermal	Long term exposure - systemic effects		0,75 mg/kg	
2,4,6-Triallyloxy-1,3,5-triazine 101-37-1	General population	oral	Long term exposure - systemic effects		0,15 mg/kg	
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Workers	inhalation	Long term exposure - systemic effects		48,5 mg/m3	no hazard identified
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Workers	dermal	Long term exposure - systemic effects		13,9 mg/kg	no hazard identified
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	General population	inhalation	Long term exposure - systemic effects		14,5 mg/m3	no hazard identified
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	General population	dermal	Long term exposure - systemic effects		8,33 mg/kg	no hazard identified
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	General population	oral	Long term exposure - systemic effects		8,33 mg/kg	no hazard identified
methacrylic acid 79-41-4	Workers	Inhalation	Long term exposure - local effects		88 mg/m3	no potential for bioaccumulation
methacrylic acid 79-41-4	Workers	Inhalation	Long term exposure - systemic effects		29,6 mg/m3	no potential for bioaccumulation
methacrylic acid 79-41-4	Workers	dermal	Long term exposure - systemic effects		4,25 mg/kg	no potential for bioaccumulation
methacrylic acid 79-41-4	General population	Inhalation	Long term exposure - local effects		6,55 mg/m3	no potential for bioaccumulation
methacrylic acid 79-41-4	General population	Inhalation	Long term exposure - systemic effects		6,3 mg/m3	no potential for bioaccumulation
methacrylic acid 79-41-4	General population	dermal	Long term exposure - systemic effects		2,55 mg/kg	no potential for bioaccumulation
maleic anhydride 108-31-6	Workers	inhalation	Acute/short term exposure -		0,2 mg/m3	

			systemic effects			
maleic anhydride 108-31-6	Workers	inhalation	Acute/short term exposure - local effects		0,2 mg/m3	
maleic anhydride 108-31-6	Workers	inhalation	Long term exposure - systemic effects		0,081 mg/m3	
maleic anhydride 108-31-6	Workers	inhalation	Long term exposure - local effects		0,081 mg/m3	
maleic anhydride 108-31-6	Workers	dermal	Acute/short term exposure - systemic effects			
maleic anhydride 108-31-6	Workers	dermal	Acute/short term exposure - local effects			
maleic anhydride 108-31-6	Workers	dermal	Long term exposure - systemic effects			
maleic anhydride 108-31-6	Workers	dermal	Long term exposure - local effects			

Biological Exposure Indices:
None

8.2. Exposure controls:

Engineering controls:
Ensure good ventilation/extraction.

Respiratory protection:
Ensure adequate ventilation.
An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area
Filter type: A (EN 14387)

Hand protection:
Chemical-resistant protective gloves (EN 374).
Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):
nitrile rubber (NBR; >= 0.4 mm thickness)
This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:
Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.
Protective eye equipment should conform to EN166.

Skin protection:
Wear suitable protective clothing.
Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:
The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.
Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form	liquid
Colour	Blue
Odor	Acrylic, Mild
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Solidification temperature	< -30 °C (< -22 °F)
Initial boiling point	> 150 °C (> 302 °F)None
Flammability	non flammable
Explosive limits	Not applicable, The product is not flammable.
Flash point	100 - < 200 °C (212 - < 392 °F); None
Auto-ignition temperature	Not applicable, The product is not flammable.
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product is non-polar/aprotic.
Viscosity (kinematic) (40 °C (104 °F);)	> 20,5 mm2/s ;.no method / method unknown
Viscosity, dynamic (Brookfield; Instrument: RVT; speed of rotation: 20 min-1; Spindle No: 3)	1.300,0 - 3.000,0 mPa.s LCT STM 10; Viscosity Brookfield
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Slight
Partition coefficient: n-octanol/water	Not applicable Mixture
Vapour pressure (27 °C (80.6 °F))	< 0,1 mm hg
Density (20 °C (68 °F))	1,08 g/cm3 no method / method unknown
Relative vapour density:	1
Particle characteristics	Not applicable Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity
Reacts with strong oxidants.
Strong bases.
Acids.
Reducing agents.

10.2. Chemical stability
Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions
See section reactivity

10.4. Conditions to avoid
Stable under normal conditions of storage and use.

10.5. Incompatible materials
See section reactivity.

10.6. Hazardous decomposition products
carbon oxides.
Hydrocarbons
nitrogen oxides
Rapid polymerisation may generate excessive heat and pressure.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Tetramethylene dimethacrylate 2082-81-7	LD50	10.066 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
2,4,6-Triallyloxy-s-triazine 101-37-1	LD50	753 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	LD50	10.837 mg/kg	rat	not specified
methacrylic acid 79-41-4	LD50	1.320 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
maleic anhydride 108-31-6	LD50	1.090 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Tetramethylene dimethacrylate 2082-81-7	LD50	> 3.000 mg/kg	rabbit	not specified
Tetramethylene dimethacrylate 2082-81-7	LD50	> 2.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
2,4,6-Triallyloxy-s-triazine 101-37-1	LD50	> 2.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Acute toxicity estimate (ATE)	> 5.000 mg/kg		Expert judgement
methacrylic acid 79-41-4	LD50	500 - 1.000 mg/kg	rabbit	Dermal Toxicity Screening
methacrylic acid 79-41-4	Acute toxicity estimate (ATE)	500 mg/kg		Expert judgement
maleic anhydride 108-31-6	LD50	2.620 mg/kg	rabbit	not specified

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	Acute toxicity estimate (ATE)	28,17 mg/l	dust/mist			Expert judgement
methacrylic acid 79-41-4	LC50	3,19 - 6,5 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
methacrylic acid 79-41-4	Acute toxicity estimate (ATE)	3,19 mg/l	dust/mist			Expert judgement

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Tetramethylene dimethacrylate 2082-81-7	not irritating	24 h	rabbit	FDA Guideline
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	not irritating	24 h	rabbit	Draize Test
methacrylic acid 79-41-4	corrosive	3 min	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
maleic anhydride 108-31-6	highly irritating		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Tetramethylene dimethacrylate 2082-81-7	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
methacrylic acid 79-41-4	corrosive		rabbit	Draize Test
maleic anhydride 108-31-6	corrosive		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Tetramethylene dimethacrylate 2082-81-7	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
methacrylic acid 79-41-4	not sensitising	Buehler test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
maleic anhydride 108-31-6	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Tetramethylene dimethacrylate 2082-81-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Tetramethylene dimethacrylate 2082-81-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Tetramethylene dimethacrylate 2082-81-7	positive without metabolic activation	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Tetramethylene dimethacrylate 2082-81-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	negative	in vitro mammalian cell micronucleus test	with and without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
methacrylic acid 79-41-4	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
maleic anhydride 108-31-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Tetramethylene dimethacrylate 2082-81-7	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
methacrylic acid 79-41-4	negative	inhalation		mouse	equivalent or similar to OECD Guideline 478 (Genetic Toxicology: Rodent Dominant Lethal Test)
methacrylic acid 79-41-4	negative	oral: gavage		mouse	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
maleic anhydride 108-31-6	negative	inhalation		rat	OECD Guideline 475 (Mammalian Bone Marrow Chromosome Aberration Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
methacrylic acid 79-41-4	not carcinogenic	inhalation	2 y	mouse	male/female	OECD Guideline 451 (Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	NOAEL P 1.000 mg/kg NOAEL F1 1.000 mg/kg		oral: gavage	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
methacrylic acid 79-41-4	NOAEL P 50 mg/kg NOAEL F1 400 mg/kg NOAEL F2 400 mg/kg	Two generation study	oral: gavage	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
maleic anhydride 108-31-6	NOAEL P 55 mg/kg NOAEL F1 55 mg/kg	Two generation study	oral: gavage	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

STOT-single exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Assessment	Route of exposure	Target Organs	Remarks
methacrylic acid 79-41-4	May cause respiratory irritation.			

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	NOAEL 1.000 mg/kg	oral: gavage		rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
methacrylic acid 79-41-4		inhalation	90 d 6 h/d, 5 d/w	rat	OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day)
maleic anhydride 108-31-6	NOAEL 40 mg/kg	oral: feed	90 d	rat	not specified

Aspiration hazard:

No data available.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

No data available.

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Tetramethylene dimethacrylate 2082-81-7	LC50	32,5 mg/l	48 h		DIN 38412-15
2,4,6-Triallyloxy-s-triazine 101-37-1	LC50	4,36 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	LC50	16,4 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
methacrylic acid 79-41-4	LC50	85 mg/l	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	EPA OTS 797.1400 (Fish Acute Toxicity Test)
methacrylic acid 79-41-4	NOEC	10 mg/l	35 d	Danio rerio	OECD Guideline 210 (fish early life stage toxicity test)
maleic anhydride 108-31-6	LC50	75 mg/l	96 h	Lepomis macrochirus	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2,4,6-Triallyloxy-s-triazine 101-37-1	EC50	19,4 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
methacrylic acid 79-41-4	EC50	> 130 mg/l	48 h	Daphnia magna	EPA OTS 797.1300 (Aquatic Invertebrate Acute Toxicity Test, Freshwater Daphnids)
maleic anhydride 108-31-6	EC50	77 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Tetramethylene dimethacrylate 2082-81-7	NOEC	5,09 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	NOEC	32 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
methacrylic acid 79-41-4	NOEC	53 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Tetramethylene dimethacrylate 2082-81-7	EC50	9,79 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
Tetramethylene dimethacrylate 2082-81-7	NOEC	2,11 mg/l	72 h	Desmodesmus subspicatus	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	EC50	> 100 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	NOEC	18,6 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
methacrylic acid 79-41-4	NOEC	8,2 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
methacrylic acid 79-41-4	EC50	45 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
maleic anhydride 108-31-6	EC50	29 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
maleic anhydride 108-31-6	EC10	23 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Tetramethylene dimethacrylate 2082-81-7	NOEC	20 mg/l	28 d	activated sludge, domestic	not specified
2,4,6-Triallyloxy-s-triazine 101-37-1	EC0	5 mg/l	3 h		OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
methacrylic acid 79-41-4	EC10	100 mg/l	17 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)
maleic anhydride 108-31-6	EC10	44,6 mg/l		Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)

12.2. Persistence and degradability

Biodegradability (Screening Tests):
The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Tetramethylene dimethacrylate 2082-81-7	readily biodegradable	aerobic	84 %	28 d	OECD Guideline 310 (Ready BiodegradabilityCO2 in Sealed Vessels (Headspace Test)
2,4,6-Triallyloxy-s-triazine 101-37-1		aerobic	> 7 - 9 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	readily biodegradable	aerobic	85 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
methacrylic acid 79-41-4	readily biodegradable	aerobic	86 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
methacrylic acid 79-41-4	inherently biodegradable	aerobic	100 %	14 d	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
maleic anhydride 108-31-6	readily biodegradable	aerobic	98 %	7 d	OECD Guideline 301 E (Ready biodegradability: Modified OECD Screening Test)

(Bio)degradability (Simulation Tests):
No data available.

12.3. Bioaccumulative potential

Partition Coefficient (octanol/water)
The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Tetramethylene dimethacrylate 2082-81-7	3,1		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
2,4,6-Triallyloxy-s-triazine 101-37-1	2,8	20 °C	not specified
2,2'-Ethylenedioxydiethyl dimethacrylate 109-16-0	2,3		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
methacrylic acid 79-41-4	0,93	22 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
maleic anhydride 108-31-6	-2,61	19,8 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

Bioconcentration factor (BCF)
No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT / vPvB / PMT / vPvM assessment

PBT/vPvB
This mixture does not contain any substances that are assessed to be a PBT or vPvB.
Based on available data, the classification criteria are not met.

PMT/vPvM
This mixture does not contain any substances that are assessed to be a PMT or vPvM.
Based on available data, the classification criteria are not met.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:
Do not empty into drains / surface water / ground water.
Dispose of in accordance with local and national regulations.

Do not spill substance/product and prevent environmental releases.
Do not rinse packaging before disposal.

Disposal of uncleaned packages:
After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.
08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

SECTION 14: Transport information

14.1. UN number or ID number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 2024/590):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable

The synthetic polymer microparticles supplied is subject to conditions laid down by entry 78 of Annex XVII to Regulation (EC) No 1907/2006 of the European Parliament and of the Council

VOC content (2010/75/EC)	< 3 %
Seveso III (2012/18/EU):	Not applicable

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text
of all abbreviations indicated by codes in this safety data sheet are as follows:

H302 Harmful if swallowed.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H372 Causes damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms:

ADG(-Code): Australian Dangerous Goods (Code)
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR : European Agreement concerning the International Carriage of Dangerous Goods by Road
ASTM: American Society for Testing and Materials
ATE: acute toxicity estimate
AS: Australian Standard
AwSV: Ordinance on Installations for the Handling of Substances Hazardous to Water
CAS: Chemical Abstract Service
CLP: Regulation (EC) No 1272/2008
CMR: cancerogenic, mutagenic or reprotoxic
DIN: German Institute for Standardization
ECx: Effective concentration (x% effective level)
ECHA: European Chemicals Agency
EC-Nummer: Substance number in the EU-inventories EINECS/ELINCS
ECTLV: European community threshold limit value
ED:Substance identified as having endocrine disrupting properties
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
EN : European Standard
ENCS: Japanese chemical inventory
EPA: US Environmental Protection Agency
EU: European Union
EU EXPLD1: Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD2: Substance listed in Annex II, Reg (EC) No. 2019/1148
EWC: European Waste Catalogue
GHS: Globally Harmonised System for Classification and Labelling of Chemicals
GLP: Good Laboratory Practice
HSNO: Hazardous Substances and New Organisms
IARC: International Agency for Research of Cancer
IATA: International Air Transport Association
IBC-Code: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
IC50: half maximal inhibitory concentration
ICAO: International Civil Aviation Organization
IMDG-Code: International Maritime Code for Dangerous Goods
IMO: International Maritime Organization
ISO: International Standardization Organisation
LC50: Median lethal concentration
LD50: Median lethal dose
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
n.o.s.: not otherwise specified
NO(A)EC: No (adverse) effect concentration
NO(A)EL: No (adverse) effect level
NZS: New Zealand Standard
OECD: Organisation for Economic Co-operation and Development
OEL: Occupational Exposure Limit
OPPT: US EPA Office of Pollution Prevention and Toxics
OPPTS: US EPA Office of Prevention, Pesticides and Toxic Substances
PBT: Persistent, bioaccumulative, toxic

PMT: Persistent, mobile and toxic
(Q)SAR: (Quantitative) structure–activity relationship
REACH: Regulation (EC) No. 1907/2006
RID: Regulations concerning the International Transport of Dangerous Goods by Rail
SADT: Self Accelerating Decomposition Temperature
SDS: Safety Data Sheet
STOT: Specific Target Organ Toxicity
STOT SE: Specific Target Organ Toxicity - single exposure
STOT RE: Specific Target Organ Toxicity - repeated exposure
SUSMP: Standard for the Uniform Scheduling of Medicines and Poisons
SVHC: Substance of very high concern (REACH Candidate List)
TRGS: German Technical Rules for hazardous substances
UN: United Nations
VOC: Volatile Organic Compound
814.018 VOC Reg CH: Swiss Ordinance 814.018 on the Incentive Tax on Volatile Organic Compounds
vPvB: Very persistent, very bioaccumulative
vPvM: Very persistent and very mobile
VwVwS: Administrative Regulation on Substances Hazardous to Waters
WGK: Water hazard class

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel´s Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,
Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.